

Product data sheet Characteristics

EY56SO332

Easy56, Socket, 3 Pin, 32A, 250V



Main Product name Easy56 Product or component Socket-outlet Device short name EY56SO332 Plug, socket category Low voltage 1P + N + E Poles description AC Network type Outlet standard Australian/New Zealand

Complementary

Surface mounted	
Straight	
32 A	
3 pins	
Tubular	
250 V	
50 Hz	
Polycarbonate: cover	
Pins: brass	
Screw terminals 416 mm² rigid or stranded cable	
16 mm	
0.471 kg	
101 mm	
101 mm	
101 mm	
Grey (RAL 7035)	
	Straight 32 A 3 pins Tubular 250 V 50 Hz Polycarbonate: cover Pins: brass Screw terminals 416 mm² rigid or stranded cable 16 mm 0.471 kg 101 mm 101 mm

Environment

Standards	AS/NZS 3123
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-2575 °C
Ambient air temperature for storage	-2575 °C

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	11.2 cm	
Package 1 Width	10.5 cm	
Package 1 Length	10.5 cm	
Package 1 Weight	532.4 g	

EU RoHS Directive

Under investigation