

Product data sheet Characteristics

EY56SO532

Easy56, Socket, 5 Pin, 32A, 500V



Main Product name Easy56 Product or component Socket-outlet Device short name EY56SO532 Plug, socket category Low voltage 3P + N + E Poles description AC Network type Outlet standard Australian/New Zealand

Complementary

| Surface mounted | |
|---|--|
| Straight | |
| 32 A | |
| 5 pins | |
| Tubular | |
| 500 V | |
| 50 Hz | |
| Polycarbonate: cover | |
| Pins: brass | |
| Screw terminals 416 mm² rigid or stranded cable | |
| 16 mm | |
| 0.471 kg | |
| 101 mm | |
| 101 mm | |
| 101 mm | |
| Grey (RAL 7035) | |
| | Straight 32 A 5 pins Tubular 500 V 50 Hz Polycarbonate: cover Pins: brass Screw terminals 416 mm² rigid or stranded cable 16 mm 0.471 kg 101 mm 101 mm |

Environment

| Standards | AS/NZS 3123 |
|---------------------------------------|-----------------------------|
| IP degree of protection | IP66 conforming to AS 60529 |
| Ambient air temperature for operation | -2575 °C |
| Ambient air temperature for storage | -2575 °C |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|---------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 11.4 cm | |
| Package 1 Width | 10.6 cm | |
| Package 1 Length | 11.0 cm | |
| Package 1 Weight | 558.0 g | |

EU RoHS Directive

Under investigation