

Product data sheet Characteristics

EY56SW120LE

Easy 56, Switch, 1P, 20A, 250V, Less **Enclosure**



Main

Man	
Product name	Easy56
Device short name	EY56SW120LE
Product or component type	Switch
Poles description	1P
Network type	AC
Network frequency	50 Hz
Control type	Rotary knob
Rotary handle padlocking	2 padlocks
Handle colour	Grey

Complementary

[Ue] rated operational voltage	250 V AC 50 Hz	
[Ithe] conventional enclosed thermal current	20 A	
[le] rated operational current	20 A (AC-21A) at 250 V 20 A (AC-23A) at 250 V	
Suitability for isolation	Yes	
Connections - terminals	Screw terminals116 mm² - rigid or stranded	
Height	101 mm	
Width	101 mm	
Net weight	0.191 kg	
Colour	Body: grey (RAL 7035) Rotary handle: dark grey	

Environment

Standards	AS/NZS 3133
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-2575 °C

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	7.7 cm	
Package 1 Width	10.0 cm	
Package 1 Length	10.0 cm	
Package 1 Weight	201.0 g	

Offer Sustainability

REACh Declaration	
Not compliant	
Yes	
China RoHS Declaration	
₽¥Yes	
	Not compliant Yes China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability of these products for specific user applications. This characteristic is not integrated to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.