



CLARE S9062TC/S - 10W

Recessed LED downlight with sensor control and selectable CCT.

Application

Ideal for interior service areas, bathrooms and storage spaces

Design Specifications

- Selectable CCT 3000K / 4000K / 5700K
- Integral PIR sensor control with a fixed 90 seconds ON motion detection function incorporating a light sensor function to engage when the lighting levels are <20lux
- Integral non-dimmable LED 10 watt control gear, IC - 4 rated.
- Designed with flex and plug for easy installation
- Stylish white trim and opal polycarbonate diffuser
- Cut - out 92mm



Performance

- In Built Sensor - **YES**
- Sensor Type - **PIR**


Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9062TC/S	240	10	760/800/850	3000/4000/5700	90
CRI	Body Colour	Cut Out (mm)		Dim (mm)		
80	WHITE	92		115(W) x 73(H)		

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

S9062TC-S CUT - OUT 92mm




Model No.	Input (V/AC)	Power (W)	Lumens (lm)	100% Current (A)	100% Current (°C)	CB	CCT (K)	Beam Angle (°)	Beam Dia (mm)	Dimension (mm)
S9062TC/S	240/230	10	760 / 800 / 850	0.06	141A Max. @ 400µs	> 50	3000/4000/5700	White	0.2	Ø115 x 73
Power (W)	Input (V/AC)	Detection Distance (m)	Detection Motion Speed (m/s)	Detection Angle	Working Humidity (RH)	Temp Setting (°C)	Light Control (lux)	Installation Height (m)	Sensor Type	
10 (100% IRL)	240/230	4m @ 20°C	0.3-1.5	120°	0-95%	* 90 ± 5	0-20	2.5	PIR	

*It will turn off in 90 seconds if there is no motion detected.



Photometric Data

Unit: cd C0/C180 — C90/C270 —



THE SFI SYSTEM ELIMINATES LED FLICKERING.

**SIMPLY
MATCH THE
ECO GEM SFI
DOWNLIGHT
WITH THIS
SDD400SFI
DIMMER.**



**DIM with
FLICKER
CONTROL**

For related
products
please
scan me

