





PREMIER S9071TC - 10W

Dimmable IP64 10W LED downlight with selectable colour temperature

Application

Ideal for any residential, retail or commercial interior space

Design Specifications

- Premium aluminium body profile, IC-4 rated
- Stylish white or silver powder coat finish
- Quality opal polycarbonate diffuser
- High efficiency SMD LED chips
- Remote constant current trailing edge dimmable LED driver, with flex and plug

Performance

Dimmable - YES
Dimmer Type - Trailing edge, optional DALI

























Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	ССТ (К)	Beam Angle (°)
	S9071TC WH	240	10	800/900/900	3000/4000/5700	90
	S9071TC SL	240	10	800/900/900	3000/4000/5700	90

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)	IPART
YES	80	WHITE	92	112	57(H)	YES
YES	80	SILVER	92	113	57(H)	YES

REES	VEET
YES	YES
YES	YES


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





Dimensions

S9071TC




Photometric Data

Photometric Data

Unit: cd C0/C180_____ C90/C270____

S9071TC at 4000K





THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE ECOGEM SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER







DIM with FLICKER CONTROL

For related products please scan me



NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

