



## PREMIER S9074TC / DP - 15/20W

IP64 DUAL POWER 15/20W LED non-dimmable downlight with selectable colour temperature

### Application

Ideal for any commercial interior spaces looking for an economical lighting choice and design flexibility

### Design Specifications

- Premium aluminium body profile, CA90 rated
- Stylish white powder coat finish
- Quality opal polycarbonate diffuser
- High efficiency SMD LED chips
- Remote constant current non - dimmable LED driver, with flex and plug and integral dual power 15/20w selections



### Technical Specification

Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	Beam Angle (°)	Dimmable
S9074TC/WH/DP	240	15/20	1600/1900/1700	3000/4000/5700	90	OPTIONAL

Model No.	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)	iPART	VEET
S9074TC/WH/DP	80	WHITE	160	200	68(H)	YES	YES

Note: Lumens (lm) shown are displayed at FULL power selection

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

### Dimensions






## Photometric Data

### Photometric Data

Unit: cd C0/C180 — C90/C270 —

S9074TC at 4000K



# THE SFI SYSTEM ELIMINATES LED FLICKERING.

**SIMPLY  
MATCH THE  
ECO GEM SFI  
DOWNLIGHT  
WITH THIS  
SDD400SFI  
DIMMER.**



**DIM with  
FLICKER  
CONTROL**

For related  
products  
please  
scan me

