





#### **PANEL S9784TC/DP2** - 12/50W


LED Backlit panel with selectable CCT and power

# **Application**

Designed for commercial and office space lighting tasks.

### **Design Specifications**

- Extruded aluminium profile (RAL9016) with high efficiency opal diffuser, suitable for a range of installation types
- White powder coat finish, high efficiency Backlit LED optics, CRI >80
- Remote constant current non-dimmable LED driver, complete with flex and plug
- Selectable CCT 3000K/4000K/5700K and selectable power.
- Suspended wire or surface mount kits available
- Emergency models compliant to AS/NZS2293 with D50 spacing classification available, see SELK1500SM Interior Emergency section.





















#### **Performance**

- Dimmable OPTIONAL
- Dimmer Type Trailing edge, 1-10V, DALI / DSI

## **Technical Specification**

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	сст (к)	CRI
	S9784/306TC/DP2	240	12/24	2250/2500/2400	3000/4000/5700	80
	S9784/606TC/DP2	240	18/36	3400/3750/3650	3000/4000/5700	80
	S9784/312TC/DP2	240	18/36	3400/3750/3650	3000/4000/5700	80
	S9784/612TC/DP2	240	35/50	4750/5250/5000	3000/4000/5700	80





	Angle (°)	Dimmable	Dimmer Type	Body Colour	Dim (mm)	IPART	VEET
1	10	OPTIONAL	Trailing edge, 1-10V, DALI / DSI	WHITE	595(L) x 295(W) x 32(H)	YES	YES
1	10	OPTIONAL	Trailing edge, 1-10V, DALI / DSI	WHITE	595(L) x 595(W) x 32(H)	YES	YES
1	10	OPTIONAL	Trailing edge, 1-10V, DALI / DSI	WHITE	1195(L) x 295(W) x 32(H)	YES	YES
1	10	OPTIONAL	Trailing edge, 1-10V, DALI / DSI	WHITE	1195(L) x 595(W) x 32(H)	N/A	YES

Note (1): Lumens (lm) shown are for TOTAL system performance.

Note (2): For dimmable configurations, the CCT must be specified at the time of order and the DP function is deactivated.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





LED downlights, oysters, linear battens and profiles, track lights, strip lights, interior architectural, highbays, lamps, emergency, floodlights, exterior architectural, weatherproof, bulkheads, sensors, electrical accessories, smart lighting controls, drivers

For more information please scan me



NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168

WA: 08 9248 7458

