



## OPAL SO3700/TC/DP2 - 8/30W

LED Oyster 8 to 30 watt with selectable CCT, dual power and dimming options

### Application

A perfect choice for apartments or commercial spaces

### Design Specifications

- Selectable CCT 3000K / 4000K / 6000K
- Durable powder coated steel body profile with a high performance opal PMMA diffuser
- High efficiency LED optics, CRI > 80
- Integral constant current LED driver, refer Dimmable model numbers
- Integral dual power selection
- Two versatile profile sizes 8/16 or 15/30 watt

### Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge**
- In Built Sensor - **OPTIONAL**
- Sensor Type - **MICROWAVE**



### Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	CRI
	SO3700/30TC/DP2	240	8/16	1100/1400/1200	3000/4000/6000	80
	SO3700/40TC/DP2	240	15/30	2350/2800/2400	3000/4000/6000	80
	SO3700/30TC/DPD	240	8/16	1100/1400/1200	3000/4000/6000	80
	SO3700/40TC/DPD	240	15/30	2350/2800/2400	3000/4000/6000	80



Dimmable	Beam Angle (°)	Body Colour	Diameter (mm)	Dim (mm)	IPART
NO	120	White	310	78(H)	YES
NO	120	White	390	102(H)	YES
YES	120	White	310	100(H)	N/A
YES	120	White	390	112(H)	N/A

Note 1: Lumens (lm) values shown are at full power rating

Note 2: Sensor SMS830 can be used for ON/OFF control only with SO3700/40TC/DP2 (non-dimmable).

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

# PIXIE AMBIENCE, CHANGE YOUR STYLE.



PIXIE AMBIENCE GPO SMART SOCKET  
SPO23/BTAM



For more  
information  
please  
scan me

